

Model: [5CP2150W](#) **5CP PLUNGER PUMP**



Specs

Max Flow: **5 gpm**

Min Pressure: **100 psi**

Max Pressure: **2000 psi**

Inlet Port Size: **0.5**

Discharge Port Size: **0.37**

RPM: **1725**

Drive Type(s): **Belt**

Material: **N/A**

Description:

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of a special W770 manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. The 1725 RPM permits a close coupled installation using a bell housing and flexible coupling or direct-drive motor-pump unit.

Datasheet: [5CP2120W-2140WCS-2150W Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

Regulator

- [7082](#) - Pressure Regulator
- [6028](#) - Prrrrr-O-Lator-Sealed-NBR

Unloader

- [7850](#) - Modular Pressure Unloader
- [7535](#) - Multiple Gun Pressure Unloader

Pressure Gauge

- [6089](#) - Pressure Gauge

Pulsation Dampener

- [6029](#) - Prrrrr-O-Lator-Rechg-NBR

Inlet Filter

- [7104](#) - Inlet Filter
- [7104.4](#) - Inlet Filter

Flexible Inlet Hose

- [990860](#) - Flexible Inlet Hose

Flexible Discharge Hose

- [990834](#) - Flexible Discharge Hose